



Repulpable Single-Coated Splicing Tape 910

Technical Data

March, 2014

Product Description

3M™ Repulpable Single-Coated Splicing Tape 910 is a single-coated repulpable construction using a release coated, semi-bleached kraft paper backing and a blue, high performance adhesive.

Product Construction

Backing	Adhesive	Color	Standard Roll Length
Semi-bleached kraft paper with a one-side, easy-release treatment	Blue, repulpable	Off-white	55 m (60 yds.)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Repulpability:	Completely*
Tensile Strength:	Machine Direction – 53 lbs./in. (600 N/100 mm) Cross Direction – 24 lbs./in. (270 N/100 mm)
Tape Thickness:	3.6 mils (0.09 mm)
Bonding Strength:	Delaminates most papers (especially for LWC coating formulations, however, adheres well to many other papers too).
Heat Resistance:	Excellent to 400°F (204°C) web temperature**

*Repulpability judged according to TAPPI UM-213, Procedure A.

**As tested in laboratory, however, heat resistance may depend on machine and web tensions, nature of paper surface, application pressure, etc. which are outside 3M control.

Features

- Water solubility and alkali dispersability are excellent and eliminate risk of contaminating the paper mill broke with non-repulpable materials.
- All components of the adhesive and backing meet the requirements of indirect food additive regulations as described under 21 CFR 176.170 (Components of paper and paperboard in contact with aqueous and fatty food) and 21 CFR 176.180 (Components of paper and paperboard in contact with dry foods).
- Packing in sealed plastic bags helps assure constant moisture content of unused tape.
- Coatings and inks do not anchor to the backside of this tape.

3M™ Repulpable Single-Coated Splicing Tape

910

Application Techniques	For optimum results, firm, even rub down pressure should be applied to the taped area to create the best possible adhesion between the tape and paper surface. A plastic squeegee or similar tool can help achieve the proper uniform pressure.
Application Ideas	<ul style="list-style-type: none">• Butt splicing coated and uncoated papers, and paper products. It has also performed well in many other finished splice applications, even with “alkaline coatings” and with stearate sizing.• Taping to the “lip” on safety splices and the “lip” and “tail” on perfect splices.• Paster hold down tabs.
Storage	Store under normal conditions of 70°F (21°C) and 50% R.H. in the sealed plastic bags until ready for immediate use.
Shelf Life	To obtain best performance, use this product within 18 months from date of manufacture.
Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.
Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2008

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2014 (3/14)