



The Right Connection®

Data Sheet

Brass Pipe Fittings



Brass Pipe Fittings

163	Hex Head Plug
165	Close Pipe Nipple
166	Long Pipe Nipple
169	90° Male Pipe Elbows
172	Male Union - NPSM x NPTF
174	Adapter-Male NPSM x Female NPTF
176	Male Union - NPSM
207-BH	Bulkhead Anchor Coupling
211	Square Head Plug - Low Lead
213	Pipe Cap
219	Hex Socket Plug - Low Lead
228	Female Cross
302	90° Female Elbow
304	90° Street Elbow
306	45° Street Elbow
322	Female Tee
324	Male Branch Tee
326	Street Tee
370	Male Hex Nipple
371	Female Hex Coupling
373	Reducer Bushing
375	Adapter-Female x Male
377	Reducing Adapter-Double Female
379	Male Reducing Hex Nipple

Compliances:

- Meets functional requirements of SAE J530, J531
- Reference: 130137, 130138, 130139, 130140, 130238, 130239, 130339, 130424, 30425, 130438

Compatible Piping Products:

- Use with brass, copper or iron pipe

Materials:

- Brass: Alloy 360, 353 for straights
- Brass: Alloy 377 for forged shapes
- Brass: Alloy C3604 for extruded shapes
- Brass Alloy: CA2745, C46400, 260 and 270 for Lead Free Brass (parts ending in LF)
- Plating: Optional electroless nickel

Performance:

- Working pressure and temperature range -65°F to +250°F at 1000 PSI
- Vacuum: Not rated

Applications / Markets:

- For any low to medium pressure line connection and non-potable water service
- "LF" lead free option for potable water

Strengths/Features:

- NPSM unions and adapters also available
- Size range from 1/8" to 1" for most products
- 148 available products
- Special sizes, configurations and thread specifications available on request.

Dixon Brass

ph 800.323.4440

fx 800.628.7259

customer.service@dixonbrass.com

dixonvalve.com