

Thread Sealant Paste


Features:

- temperature range: **-300°F to 500°F**
- do not use with oxygen

Size	Part #	Price/E	Opt Qty
¼ pint	LCTS14	\$14.75	24
½ pint	LCTS1	21.55	24
1 pint	LCTS2	33.75	12
1 quart	LCTS3	60.35	12

Joint Sealant Gasket Material

Features:

- GORE-TEX® interchangeable
- Form-In-Place expanded PTFE gasket material with adhesive backing
- manufactured from 100% virgin PTFE
- unaffected by all common chemicals (pH from 0-14)
- unlimited shelf life
- resilient with low cold flow
- requires less force than standard gasket materials
- pressure range: vacuum to 3000 PSI
- temperature range: **-450°F to 600°F**
- made in the USA
- FDA compliant #21CFR177.1550
- larger spools are available, consult Dixon™ for price and availability



Size	Length	Part #	Price/E
¼"	20'	LCJS4-20	\$69.45
¼"	50'	LCJS4-50	159.55
⅜"	25'	LCJS6-25	127.50
½"	15'	LCJS8-15	127.50
¾"	15'	LCJS12-15	291.85

Leak Detector

Features:

- detects leaks by forming bubbles which remain for up to ten minutes
- will not cause corrosion or deterioration
- color: fluorescent yellow
- non-toxic, non-freezing
- temperature range: **-7°F (-20°C) to 180°F (82°C)**
- meets Federal specification MIL-L-25567-C



Size	Part #	Price/E	Case Qty
8 oz.	LCLD	\$11.90	24

Dixon™ Coupling Lubricant

Application:

- For use in assembly operations involving natural or synthetic rubber or plastic. Also an excellent lubricant when rubber or plastic needs to be cut, machined, pressed, turned, trimmed or ground. Once coupling lubricant dries, slipping action goes away.

Feature:

- biodegradable lubricant for coupling shanks, O-rings, hoses, sleeves, rubber washers and grommets.



Size	Part #	Price/E
1 liter	DCL20	\$36.50
4 liters	DCL80	94.50

WD-40 Smart Straw

Features:

- permanently attached straw
- flip up for a precision spray; flip down for regular spray action
- sold in case quantities only
- should not be used as a lubricant for coupling shanks



Size	Part #	Price/E	Case Qty
11 oz.	WD40	\$21.00	12