

SAFETY DATA SHEET

1. Identification

Product identifier Hercules Glug Kitchen - Liquid

Other means of identification

Product code 7302E

Synonyms Part Numbers: 20470, 20475

Recommended use Liquid Drain Cleaner

Recommended restrictions None known.

Manufacturer Distributor

Company Name HCC Holdings, Inc. an Oatey Affiliate

Address 4700 West 160th Street 145 Walker Drive

Cleveland, OH 44135 Brampton, ON L6T 5P5, Canada

Oatey Canada Supply Chain Services Co.

Telephone 216-267-7100 E-mail info@oatey.com

Transport Emergency Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015

Contact person MSDS Coordinator

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1A

Serious eye damage/eye irritation Category 1

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

 Chemical name
 CAS number
 %

 Water
 7732-18-5
 50-80

Hercules Glug Kitchen - Liquid

SDS Canada

925655 Version #: 02 Revision date: 11-April-2018 Issue date: 21-June-2016

Sodium hydroxide	1310-73-2	10-20
Potassium hydroxide	1310-58-3	1-5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped

with a one-way valve or other proper respiratory medical device. Get medical attention

immediately.

Skin contactTake off immediately all contaminated clothing. Immediately flush skin with plenty of water. Call a

physician or poison control center immediately. Chemical burns must be treated by a physician. For minor skin contact, avoid spreading material on unaffected skin. Wash contaminated clothing

before reuse. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce

vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical

device.

Most important symptoms/effects, acute and delayed Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

In case of shortness of breath, give oxygen. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions
Specific methods

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Туре	Value	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
Sodium hydroxide (CAS 1310-73-2)	Ceiling	2 mg/m3	
ological limit values	No biological exposure limits noted for the ingredient(s).		

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Wear appropriate chemical resistant clothing. Other

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get this material on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Liquid. **Form** Color Clear. Odor None.

Not available. Odor threshold

13 pН

Melting point/freezing point Not available. Initial boiling point and boiling 212 °F (100 °C)

range

Flash point > 212.0 °F (> 100.0 °C)

Evaporation rate Not available. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Vapor pressure Not available. Not available. Vapor density

1.175 Relative density

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature**

Viscosity 10 cP

Other information

VOC

Not explosive. **Explosive properties** Not oxidizing. **Oxidizing properties**

925655

0 g/l

Hercules Glug Kitchen - Liquid SDS Canada 4/7 Version #: 02 Revision date: 11-April-2018 Issue date: 21-June-2016

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Do not mix with other chemicals. Conditions to avoid

Incompatible materials Strong acids. Acids. Oxidizing agents. Maleic anhydride. **Hazardous decomposition**

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns. **Eve contact** Causes serious eye damage. Causes digestive tract burns. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity Causes burns.

Components **Species** Test Results

Potassium hydroxide (CAS 1310-58-3)

Acute

Oral

LD50 Rat 273 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Potassium hydroxide (CAS 1310-58-3) Irritant Sodium hydroxide (CAS 1310-73-2) Irritant

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Hercules Glug Kitchen - Liquid SDS Canada 5/7

925655 Version #: 02 Revision date: 11-April-2018 Issue date: 21-June-2016 Components Species Test Results

Potassium hydroxide (CAS 1310-58-3)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 80 mg/l, 96 Hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN3266

UN proper shipping name CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide, Potassium hydroxide)

Transport hazard class(es)

Class 8
Subsidiary risk Packing group II
Environmental hazards D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN3266

UN proper shipping name

Transport hazard class(es)

Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide, Potassium hydroxide)

Class 8
Subsidiary risk Packing group II
Environmental hazards No.
ERG Code 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3266

UN proper shipping name Corrosive

Transport hazard class(es)

Corrosive liquid, basic, inorganic, n.o.s. (Sodium hydroxide, Potassium hydroxide)

Class 8
Subsidiary risk Packing group II
Environmental hazards

Marine pollutant No. EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Sodium hydroxide (CAS 1310-73-2)

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information

Issue date 21-June-2016

 Revision date

 Version #
 01

 References
 ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Disclaimer HCC Holdings Inc. an Oatey Affiliate cannot anticipate all conditions under which this information

and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).