# **SPERIAN HAND PROTECTION**

## TECHNICAL SPECIFICATIONS

### **SPERIAN TOP DOG™ GLOVES**

	PRODUCT INFORMATION				
Sizes Available	Part #	Overedge Colors	UPC	1	
Men's	KV18-55	Yellow	801462215502		
Ladies'	KV18L-55	Blue	801462215526	A	
Jumbo	KV18J-55	White	801462215519		



Shell Material:	Kevlar Armor - Kevlar and Stainless Steel blend	Material Color:	Yellow/Black
Shell Weight:	7 cut, standard weight	Leather Color:	Gray
Coating Material:	Split leather	Case Qty:	144
Coating Pattern:	NA	Country of Origin:	China

#### **PRODUCT FEATURES**

• Full premium leather palm for added protection against puncture and abrasion

• Kevlar Armor, combines Kevlar and Steel for optimal cut, slash and abrasion resistance

• Leather palm improves grip in wet and oily applications

#### **TESTING INFORMATION**

	Test Method	Level	Test Result
Abrasion Resistance:	ASTM 3389-05	Level 6	≥ 20,000 cycles
	EN388	Level 4	≥ 8,000 cycles
Cut Resistance:	ASTM F 1790-97	Level 4	≥ 1,500 grams
	EN388	not tested	
Tear Resistance:	EN388	Level 4	≥ 75 newtons
Puncture Resistance:	EN388	Level 3	≥ 100 newtons

#### LAUNDERING INSTRUCTIONS

Dry cleaning is the acceptable cleaning method for gloves of 100% KEVLAR® fiber with leather palms. Some differences in shrinkage, weight loss, yarn tensile strength, and color related to staining or the cleaning method may be seen, but there is no significant impact on cut resistance up to 30 cleaning cycles (without industrial use between cycles). Thirty cleaning cycles is considered to be more than can be expected because of normal wear.

#### / WARNINGS

\*Gloves are cut resistant - not cut proof. Extreme caution should be used around moving machinery.

\*\* Laundering gloves that have been in contact with toxic or corrosive chemicals may result in a chemical reaction, including fumes, that could cause personal injury, serious illness or death.

This information is provided as a guideline for product use. The end user is solely responsible for determining the suitability of a particular glove for a specific application and the length of time in which such glove may be safely used.

Sperian Protection Americas, Inc. | 900 Douglas Pike, Smithfield, RI 02917-1874 | tel: 1.800.430.5490 | fax: 1.800.322.1330

