




UWER 5/200 SI 120 V

Speed range: 9,000 - 20,000 RPM
Output: 0.4 HP / 300 Watts




PFERDERGONOMICS®



PFERDMEDIA

To see it in action, please visit
pferdusa.com/91200

Tool features

- U** Electric
- W** Angle grinder
- ER** Electronic speed regulation
- 5** 500 watt consumption
- 200** 20,000 RPM max. rotational speed
- SI** Double insulated 
- 120 V** 120 Volt

Accessories included

- 1 key
- 10' power cable

Tool benefits

- For grinding and finishing work using COMBIDISC® products (use backing pad without shank).
- High output, convenient to use.
- Spindle with 1/4"-20 UNC thread.
- Digital electronic speed control ensures constant RPM even under load.
- Restart protection on power failure.

EDP number	Model number	Rotational speed [RPM]	Voltage 50-60 Hz	Power consumption [watts]	Power output [watts]	Spindle thread	Max. Amps	Sound level [dB(A)]	Weight [lb]
91200	UWER 5/200 SI 120 V	9,000 - 20,000	120	500	300	1/4-20	4.6	83	2.98









Spindle extension (20 mm)

	Model number	Product mounting	EDP number
	SPV 20 CD 1/4-20 UNC	COMBIDISC® holder without threaded shank	95808

Keys

	Width	Qty	EDP number
	14 mm	1	93340

Recommended PFERD products

Catalogue 204			
COMBIDISC® Mini-POLIFAN® discs 2" to 3" diameter COMBIDISC® abrasive discs 1" to 2" diameter COMBIDISC® diamond discs 1" to 1-1/2" diameter	  	COMBIDISC® brush 2" diameter COMBIDISC® non-woven discs surface conditioning, hard type 1-1/2" diameter	  
		COMBIDISC® unitized discs 2" to 3" diameter COMBIDISC® textile discs 2" diameter	 

Note: Product recommendations are based on general peripheral and rotational speeds.

Please consult the appropriate catalogue section for technical information on specific recommended speeds based on application, abrasive grain, product size/shape, and workpiece material.

Comply with ANSI B7.1-2000 standards and OSHA regulations.