

**PRODUCT NUMBER: PF570****Pure Fit PF570**

Lightweight, gray HPPE and stainless steel strand liner, and HPPE and Spandex plated interior, with gray nitrile palm and fingertip coating

**Overview****Reference Number**

PF570

**Product Type**

Gloves

**Range**

cut and puncture protection

**Line**

Cut resistant

**Brand**

Sperian

**Brand formerly known as**

PERFECT FIT

**Industry**

- Automotive and Part Manufacturer
- Building and Construction
- Fishing
- General Industry
- Glass Industries
- Iron and steel industry
- Maintenance
- Metal steel
- Paper Industries
- Ship Building
- Telecoms
- Wood Industries

**Product Use**

Construction • Recycling • Lumber and Mill Work • Glass Handling • Metal Stamping • Automotive Assembly  
• Landscaping

**Features & Benefits****Feature**

HPPE fiber is lightweight, and low-linting.

**Benefit**

Pure Fit HPPE, low-linting fiber gloves are excellent protection for worker and product.

**Feature**

HPPE and stainless steel strand blended knit glove.

**Benefit**

HPPE and stainless steel provides excellent cut and slash protection.

**Feature**

HPPE and Spandex blend interior plating

**Benefit**

Fiber blend increases wearer comfort and improves the fit and form of the glove

**Feature**

Nitrile palm and fingertip coating.

**Benefit**

Nitrile provides added cut, abrasion and snag protection.

## Technical Description

**Description**

Lightweight, gray HPPE and stainless steel, with gray nitrile palm and fingertip coating.

**Product Technology**

Pure Fit

**Fiber**

HPPE (High Performance Polyethylene) and stainless steel

**Gauge**

13 gauge

**Glove/liner color**

Gray

**Coating Type**

Nitrile

**Coating Color**

Gray

**Sizes**

Small, Medium, Large, and XLarge

**OE Color**

Small = Red Medium = Blue Large = Yellow XLarge = White

## EN 388 - Mechanical Hazards Abrasion Resistance

|                                 |   |
|---------------------------------|---|
| Abrasion resistance             | 4 |
| Cutting resistance (Coupe test) | 5 |
| Tear resistance                 | 4 |
| Puncture resistance             | 3 |

## ASTM D3389-05

|                                |         |
|--------------------------------|---------|
| ANSI Level Abrasion Resistance | Level 4 |
|--------------------------------|---------|

## ASTM F1790-97

|                           |         |
|---------------------------|---------|
| ANSI Level Cut Resistance | Level 4 |
|---------------------------|---------|

## Packaging Label

**UOM**

Pair

## Certifications

**Quality Assurance**

ISO 9001 / 2000

## Maintenance

### Storage Information

Store in cool dry place away from direct sunlight.

### Care Instructions

Product withstands commercial laundry-room detergents (up to pH15) and warm water temperatures up to 120° F (49° C). Lower heat settings (up to 180° F) are suggested for drying as extreme heat may cause shrinking and degradation of fiber. HPPE fiber can be bleached without harming the mechanical properties.

## Packaging

### Unit of Measure

Pair

### Quantity per Box/Pack/Case

144

### Quantity for Minimum Order

12

### Country of Origin

Pakistan

© Honeywell International Inc.