



TRIM[®] TC 155

Nonferrous Corrosion Inhibitor

GENERAL DESCRIPTION

TRIM[®] TC 155 is a nonferrous corrosion inhibitor for use in water soluble and straight oil systems. It is particularly effective in preventing staining and white rust on die cast alloys containing copper.

APPLICATION GUIDELINES

- TC 155 is added at a rate of 0.05%-0.125% to working solutions.
- This product should not be used in conjunction with systems containing copper or copper amine compounds as part of their formulation or systems to which these compounds have been added.

HEALTH & SAFETY

See the most recent SDS at 2trim.us/s/?i=1276-en-US-US.



TECHNICAL ASSISTANCE

- For additional product applications information including performance optimization, please contact your Master Chemical Authorized Distributor at 2trim.us/distributors.php, your District Sales Manager, the Tech Line at 1-800-537-3365, or visit our web site at www.masterchemical.com.
- Packaging: North America – 1-gallon container, 5-gallon pail, and 54-gallon drum
- Europe/Asia: 20-litre pail and 204-litre drum.

PHYSICAL PROPERTIES (TYPICAL DATA)

Form	Liquid	Flash Point	108°C (226°F) (ASTM D92-12B)
Color	Amber	Odor	None
Residue	Oily		

The information herein is given in good faith and believed current as of the date of this Data & Information sheet and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Chemical Corporation for further information. For the most recent version of this document, please go to this URL: 2trim.us/di/?i=81.

TRIM[®] is a registered trademark of Master Chemical Corporation

© 2006-2015 Master Chemical Corporation • Revised 10/14/15